

Extreme-duty torque wrenches for heavy-duty applications

PNEUMATIC




30 years of experience in gearbox engineering and design has brought about our latest generation in planetary gearboxes – RAD Single Speed. Designed for extreme-duty use in a variety of industries worldwide, RAD Single Speed torque wrenches offer:

FEATURES

- The ultimate in power-to-weight ratio
- Wide torque range to suit multiple applications
- Unmatched reliability delivered by one of the most advanced engineered gear boxes on the market
- Controlled torque - accuracy of +/- 4% and repeatability of +/- 2%

FRL UNIT

- Low weight tool holder made from high-density polypropylene
- Includes pressure gauge, filter, regulator and oiler



IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.) LOW HIGH	RPM	WEIGHT (lbs.)	NOISE LEVEL	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
12316	RAD 350SL	0.75"	50 350	47	6	80 db	6.6"	2.4"	2.75"	8.75"
12814	RAD 7GX	0.75"	100 700	22	8	80 db	9.0"	2.5"	2.75"	9.0"
12818	RAD 10GX	0.75"	200 1000	10	8	80 db	8.15"	2.5"	2.75"	8.07"
17328	RAD 15DX	1.0"	300 1500	10	8.6	80 db	8.0"	2.7"	2.75"	8.1"
12377	RAD 25GX	1.0"	500 2500	9	13.5	85 db	9.7"	3.1"	3.3"	9.5"
22238	RAD 30DX	1.0"	900 3000	8	14.8	85 db	10"	3.2"	3.3"	9.5"
12356	RAD 34GX*	1.0"	1000 3400	10	20	85 db	12.5"	3.4"	3.7"	10.8"
20248	RAD 50DX	1.5"	1500 5000	6	23.5	85 db	11.25"	3.75"	3.75"	10.4"
15328	RAD 60DX	1.5"	2000 6000	5	27.6	85 db	13.7"	4.0"	4.0"	10.9"
18558	RAD 80DX	1.5"	2500 8000	4	30.5	85 db	12.15"	4.25"	4.25"	10.65"
26152	RAD 110DX	1.5"	4000 11000	3	42	85 db	13.9"	5.0"	5.0"	11.07"

METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW HIGH	RPM	WEIGHT (Kg)	NOISE LEVEL	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
13573	RAD 475SL-M	0.75"	70 475	47	2.7	80 db	167	61	70	222
13539	RAD 10GX-M	0.75"	150 950	22	3.6	80 db	228	63	70	228
13549	RAD 14GX-M	0.75"	275 1400	10	3.8	80 db	228	63	70	228
19135	RAD 20DX-M	1.0"	400 2000	10	4.0	80 db	203	69	70	228
13565	RAD 34GX-M	1.0"	700 3400	9	6.1	85 db	240	78	83	241
24717	RAD 40DX-M	1.0"	1200 4000	8	6.7	85 db	254	81	83	241
13571	RAD 46GX-M*	1.0"	1400 4600	10	9.0	85 db	317	86	94	274
26133	RAD 70DX-M	1.5"	2000 7000	6	10.6	85 db	285	95	95	264
15805	RAD 80DX-M	1.5"	2700 8000	5	12.4	85 db	348	101	101	276
23229	RAD 110DX-M	1.5"	3400 11000	4	13.7	85 db	308	108	108	270
26153	RAD 150DX-M	1.5"	5500 15000	3	18.9	85 db	353	127	127	281

Accuracy of +/-4%, Repeatability of +/-2% | *Also available in a 1.5" square drive.