

RAD CALIBRATION SYSTEMS

TRANSDUCER FEATURES

- Ranges up to 7,000 ft. lbs./ 9,500 Nm
- Screen on transducer allows for convenient reading
- Connect to RAD Torque Transducer Software via your computer or tablet
- Classified to BS 7882:2017 as Class 1 or better for the primary range (+/-0.5% of reading from 20% to 100% of full scale)



TRANSDUCER



SMALL CALIBRATION SYSTEM

IMPERIAL

PART NUMBER	DESCRIPTION	TORQUE (ft. lbs.)		DRIVE SIZE	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C
		LOW	HIGH					
23442	RAD CALIBRATION SYSTEM 1500	75	1500	1.0"	4	11.75"	11.53"	5.50"
23443	RAD CALIBRATION SYSTEM 3500	175	3500	1.5"	10	14.50"	13.53"	7.00"
23444	RAD CALIBRATION SYSTEM 7000	350	7000	1.5"	11	14.50"	13.53"	7.00"

METRIC

PART NUMBER	DESCRIPTION	TORQUE (Nm)		DRIVE SIZE	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)
		LOW	HIGH					
23442	RAD CALIBRATION SYSTEM 1500	100	2000	1.0"	1.8	298	293	140
23443	RAD CALIBRATION SYSTEM 3500	250	4750	1.5"	4.5	368	344	178
23444	RAD CALIBRATION SYSTEM 7000	475	9500	1.5"	4.9	368	344	178

